



HEAVY MOVABLE
STRUCTURES, INC.

FIFTH BIENNIAL SYMPOSIUM

November 2nd - 4th, 1994

Holiday Inn Surfside
Clearwater Beach, Florida

SESSION WORKSHOP PRESENTATIONS


"145th STREET BRIDGE REPAIR"

by MICHAEL S. HERSHEY, P.E.
New York City DOT, Bureau of Bridges

DISCLAIMER

It is the policy of the Corporation to provide a means for information interchange. It does not propagate, recommend or endorse any of the information interchanged as it relates to design principles, processes or products presented at the Symposium and/or contained herein. All Data are the author's and not the Corporation's. Application of information interchanged is the responsibility of the user to validate and verify its integrity prior to use.

145 th STREET BRIDGE REPAIR



NEW YORK CITY DEPT. OF TRANSPORTATION
BUREAU OF BRIDGES

MICHAEL S.HERSHEY, P.E.
DIRECTOR BRIDGE MAINTENANCE
NOVEMBER 1994

145TH STREET BRIDGE REPAIR

TABLE OF CONTENTS

<u>Section</u>	<u>Page (s)</u>
I BACKGROUND	1
II DESCRIPTION OF THE FIRE DAMAGE	1 - 2
III DESCRIPTION OF THE BRIDGE STRUCTURE	2
IV PLANNING THE REPAIR	2 - 3
V DESCRIPTION OF THE REPAIR	3 - 4
1. Jacking System Description	5
2. Monitoring the Loads and Stresses	5
3. Temporary Chord Members	6
4. Sequence for Jacking and Replacement of the Damaged Chord	6 - 7
5. Means to Control Jacking Process	7 - 8
6. Structural Repair	8 - 9
7. Jacking Operation	9 - 10
8. Installation of New Chord	10
VI SUMMARY	11
APPENDIX	

145th STREET BRIDGE REPAIR

I BACKGROUND

The 145th Street Bridge is located in New York City on the Harlem River. It connects 145th St. in Manhattan with 149th St. in the Bronx. This swing bridge is supported on masonry piers on either side of the river and by a circular drum girder atop a masonry pier in the middle of the river channel. To allow for passage of waterway vessels the bridge opens by swinging or rotating 90° about the center drum girder, creating 2 channels each 104 feet wide. The bridge can turn because it sits on 72 steel rollers sandwiched between the center drum girder and the masonry pier.

Originally constructed in 1903, this bridge lies between the Madison Avenue Bridge to the south and the Macombs Dam Bridge to the north. Orientation of the bridge is east-west.

II DESCRIPTION OF THE FIRE DAMAGE

On June 8, 1993, a major fire occurred in the lower portion of the drum girder. The fire was not detected for several hours resulting in extensive damage to the machinery room timber floor, walls and mechanical and electrical system. Due to the containment provided by the bridge deck above, the circular steel drum girder on the sides, the masonry pier below and fueled by the timber floor, the fire caused temperatures within this space that were high enough to cause steel members to yield. The damage caused by the fire included:

- buckling of middle truss lower chord
- buckling of distribution girder bracing angles
- melting of electrical wiring
- destruction of electrical relays, contactors, etc.
- loss of machinery room floor and walls
- peeling of paint from steel members
- possible loss of drive motors

The initial bridge inspection concluded that the structure was still sound enough to carry vehicular loads and the bridge was reopened to land traffic within a short period of time. Operation of the bridge for waterway traffic was not so easily achieved.

Operation of the bridge for waterway traffic was not possible due to the following reasons:

- buckling of lower chord of middle truss at the center of the bridge
- loss of electrical system
- undetermined condition of drive motors and mechanical components
- extensive debris in lower drum girder area

To permanently restore the bridge to full operation would require complete replacement of the electrical system, rehabilitation of the mechanical system and structural repairs. This process in New York City would normally take approximately at least two to three years considering the need to hire a consultant to prepare the scope, award a design contract to another consultant to prepare drawings and specifications and award the project to a contractor for construction. This time frame would not be acceptable to the Coast Guard who would consider the inability to restore operation of the bridge as urgently as possible a violation of federal law and subject the City to civil and possible criminal penalties.

III DESCRIPTION OF BRIDGE STRUCTURE

The superstructure of the 145th St. Bridge is supported by three longitudinal trusses: south truss, center truss and north truss. The ends of the trusses at the Manhattan and Bronx piers sit on independent end lifts, three per pier, six total. End lifts are mechanical bearing devices that either retract or raise off the support pier to permit a swing bridge structure to cantilever out from its central support prior to opening. In the case of this bridge, the end lift is an eccentric wheel that when rotated lifts clear of its support and "floats" about 2 1/4 inches above the base plate. Each end lift has an independent drive motor. In normal operation, all three end lifts on each end of the bridge are raised or lowered simultaneously.

The bridge roadway deck is a concrete-filled steel grating. The deck is supported on longitudinal steel stringers spaced 4 feet apart. These stringers are welded at their end connections providing continuity in the longitudinal direction. At the center of the bridge there are deep distribution girders below the roadway. The stiffening effect of the concrete-filled bridge deck, continuous stringers and deep distribution girders, although not included in the original calculations, became significant factors during the repair as will be discussed later.

IV PLANNING THE REPAIR

The consulting engineering firm of Hardesty and Hanover was called in immediately after the fire to make an assessment of the damage and condition of the bridge. Hardesty and Hanover was quite familiar with the bridge due to their involvement in inspection and preparation of the BRPR for 145th St. A major fire such as occurred here was likely to have significant impact on the final BRPR.

Both Hardesty and Hanover and our in-house maintenance department recognized the need to find an interim solution to restore the bridge to operation. From our collective knowledge of the existing condition of the bridge and recent rehabilitation, the following minimum repairs would be required to restore the bridge to temporary operation:

1. Rebuild machinery room floor and walls to provide a safe and secure enclosure. This would require extensive debris removal of fire-damaged material from the lower drum girder area.

2. Installation of complete electrical system for power, control, lighting and heating. For this work we had good quality electrical drawings from the recent 1986 rehabilitation.
3. Installation of temporary drive system. We had in our storage facility the 10 HP motor that was used for temporary operation of the bridge during the 1986 rehabilitation. Although undersize and requiring substantially more time than the main drive motors to open the bridge, this small motor had performed quite well for the infrequent openings during the bridge rehabilitation.
4. Steel repair of buckled lower chord at midspan of the center truss. Although similar to other steel repairs performed routinely by the Bureau of Bridges, repair of a primary load-carrying member in a main truss would require significant and careful planning, engineering and attention to details. One of the most challenging feats to the structural engineer with little margin for error is the replacement of a critical part of a load-bearing structure while under load.

The above mechanical, electrical and structural repairs were all within the ability of our in-house maintenance section responsible for the Harlem River Bridges. Before a decision to proceed could be made, however, it was necessary for the Engineer to develop a scheme for the steel repair. Hardesty and Hanover prepared the steel repair details and presented it to us at a meeting in June 1993. It became clear at this meeting that we had the in-house capability to do the repairs and restore the bridge to service with a cooperative effort; Hardesty and Hanover as the Engineer and Bureau of Bridges Maintenance Division as the Contractor. I requested permission to repair this bridge as an in-house project and obtained approval from Chief Engineer Fred Pascopella and Assistant Commissioner Frank Gallo.

The assignment of responsibilities was as follows:

- 1) Engineering by Hardesty and Hanover
- 2) Jacking and strain gages by the in-house Mechanical Section under Nick Dini
- 3) Mechanical, electrical and structural fabrication and installation by the Harlem River Bridge section under Hassan Eldessoky.

V DESCRIPTION OF THE REPAIR

To repair an existing structural member under load, it is necessary to ensure that the repair process itself will not cause a failure of the member or any other part of the structure. This is normally accomplished by various approaches, such as: reducing live load, relieving dead load via shoring or strong backs, providing temporary members, etc. In the case of the 145th St. Bridge as part of a 300' load-carrying truss, it would be essential to design a repair procedure that would allow for removal of part of the lower chord without overloading any other truss members, while maintaining the geometry of the truss. In addition, the procedure had to allow for small adjustments to the truss geometry if required.

One of the major decisions we faced was whether to install the replacement chord in one 24ft. length or in two 12ft. sections. The engineer originally proposed to install the replacement bottom chord member in two halves with a splice in the middle. The advantage in this method is primarily that it would be easier to make allowances in the field for mismatch in existing bolt holes and similar corrections for unforeseen field conditions. A disadvantage would be the additional splice plates, bolts and drilling that would be required.

We (the Maintenance section) preferred to install the steel in one piece which would require careful planning, fabrication and measuring to ensure we would match the existing end connection bolt patterns. The finished product would be neater and we considered the repair to be permanent. By choosing this more difficult approach we showed confidence in the skills and abilities of our in-house engineers and field personnel.

The main phases of the repair, would be the following:

- Remove a 33 foot by 2 foot section of concrete-filled in grating from each side of the middle lower chord to provide access for removal of damaged steel and installation of new member.
- Jack up the ends of the bridge to achieve an unloaded condition in the middle lower chord.
- Install a temporary chord member that would maintain the truss geometry during removal of the damaged steel. This temporary chord would be required to have some adjustment capability.
- Remove 24' long damaged chord member.
- Install new chord member.
- Preload new chord member and lower the bridge.
- Rewire electrical control and power system.
- Install 10 HP temporary drive motor.
- Test bridge.
- Restore bridge deck.

In order to reduce the load to near-zero in the middle panel of the lower chord, it was necessary to jack the bridge at the end abutments. This would unload the lower chord. It was anticipated that to achieve a near-zero load in the bottom chord, a jacking force of 200 kips at each end lift would produce approximately 595 kips in the bottom chord. The jacking height would be about three inches. A jacking system was designed by our in-house mechanical section to accommodate these requirements.

1. Jacking System Description

The jacking system is comprised of twenty four individual jacks, four per end lift. Each jack is rated at 50 tons and has a stroke of only 5/8" due to the limited clearance we had to work with. These jacks were situated on the end lift base plate in such a manner that they were overhanging the edge of the base plate. To provide full bearing support under the jacks, we added the steel assemblies shown in Fig. 1. These assemblies provide an additional 1" of bearing for jacks and are held in place by the 7/8" tie rods shown. The assemblies are supported by elastomeric pads to be consistent with the existing end lift wheel base plate. This ensures that the base plate and support assemblies deflect an equal amount under the jacking load and maintains full bearing under the jacks.

At each abutment there are three end lifts with four jacks each for a total of 12 jacks. We designed the hydraulic system so that any combination of end lifts could be jacked, i.e., all three together, any two in combination or a single end lift. This was accomplished via a system of manifolds and cut off valves.

The entire system or any portion desired is driven by an electric powered hydraulic motor. A manual back-up system was provided by installing two manual pumps at each end lift station. The jacking of the bridge was actually performed using the manual pumps for reasons explained later. Details of the jacking system are shown in Fig. 2.

2. Monitoring the Loads and Stresses

Monitoring of the loads in the upper and lower chord members was accomplished via application of electrical resistance strain gages. A total of 60 strain gages were used to monitor strain at 30 different locations. Strain readings were taken during the entire course of the work including initial leveling, jacking up, steel replacement, jacking down, testing the end lifts and finally during the actual bridge opening. Locations of strain gages are shown in Fig. 6.

All readings represent change in strain relative to the initial or existing loads in the bridge prior to beginning our work. Since the existing state of strain or stress was not measured, our readings do not represent the actual strain in the truss members but the increase or decrease from a zero base line established before jacking. The only exception to this are the strain gages on the new steel lower chord. This member was installed with an initial zero load. The strain gages on this member measure the actual preload and subsequent truss loads included during jacking the bridge down.

See Fig. 3 for an example of the table prepared to record strain gage readings and jacking pressures

3. Temporary Chord Members

The object of this repair was to replace the damaged lower chord of the center truss at the middle of the bridge. It was therefore necessary to provide some means to stabilize the truss during the time the damaged chord was being removed and the new chord was being installed. To accomplish this, a three-part temporary chord was designed. This temporary chord consisted of an 8" square tube member located above the existing chord and two tee sections below and on each side. Details of the temporary chord members are shown on Figs. 4 and 5. Placement of these temporary members had to allow sufficient clearance to work on the permanent steel chord.

The upper tube member served as an adjustable strut between panel points. Adjustment was accomplished by incorporating a 100 ton hydraulic jack into the east end of the tube. After the bridge was jacked up to relieve the load in the damaged member, this strut was installed and given a preload before the damaged chord was removed. At the same time, the two tee sections were secured by tightening their connection bolts.

Although not anticipated, it became necessary to install jacks in the tee sections also. It became apparent after the damaged chord was removed that the distance between panel points was about 3/8" less than the required 24' - 0". Due to the unexpected stiffness of the lower chord, it was necessary to apply additional jacking capability to increase the distance between the panel points by even a small amount. A 50 ton jack was installed at each tee section to provide this extra force.

4. Sequence for Jacking and Replacement of the Damaged Chord

Jacking of a structure when more than one lifting point is involved (six in our case) can be done using equal force or equal displacement method.

The actual jacking procedure for the 145th Street Bridge was a combination of the equal force and equal displacement method and proved to be more complex than envisioned due to a number of factors which will be discussed later. The sequence was as follows:

1. Strain measurement instrumentation initialized and calibrated.
2. Jacking of the bridge initiated and continued until the Consulting Engineer (based on strain gage readings and jacking force calculated from the hydraulic pressure in the jacks) decided that removal of the buckled chord is safe.
3. Temporary chord bolts are tightened to prevent any change in stress/geometry when the buckled chord is removed.

4. The damaged chord is unbolted and removed. No change in the strain levels at any of the upper or lower chords is detected. The load transferred to the temporary chords is about 10 kips, "relaxation from compression" indicating that at the time of removal the damaged chord was in a mild state of tension.
5. Prior to installation of new chord, local jacking is performed using the two temporary chord tee sections equipped with 50 ton jacks and the square tubing chord equipped with a 100 ton jack. The purpose of the temporary chord jacking was to provide compression in the new member immediately after installation, prior to releasing of the main jacking system.
6. New chord is installed with only minor adjustments to the total length of webs and some normal reaming of the holes at the splices. All the bolts of the new chord are tightened prior to removing of the temporary chords.
7. Temporary chords are relaxed and the transferred load to the new chord amounts to a strain of 60 microstrains compression. The equivalent force in the chord is 183 kips.
8. Bridge is ready now for lowering back to the initial position. Jacking and removal of shims bring the bridge to the position where only the leveling shims are between the pedestal and the cams. Strain readings were taken for each lowering step and are presented in the attached tables.
9. The leveling shims are removed and bridge is seated in the final position.

5. Means to Control Jacking Process

Repair to an existing truss under load requires careful planning and monitoring of loads and stresses in critical members at all times. If one is not careful, a catastrophic failure of part or all of the structure can occur. During the repair of the 145th St. Bridge, the following means were utilized to control the jacking, removal and replacement of the lower truss chord members.

- A) Strain gages -- A total of 60 strain gages were installed on the bridge structure at the following locations: (see Fig. 6)
 - Top chord member at the center of the bridge at each of the three trusses.
 - Bottom chord member at the center of the bridge at the north and south truss.
 - Temporary chord members at the center of the bridge in the middle truss - temporary chord comprised of 8" square tube and two tee sections.
 - New bottom chord member being installed in center middle truss for this repair.

- B) Jacking hydraulic pressure -- loads being introduced into the structure are measured indirectly by knowing the jack hydraulic pressure. By constantly monitoring the pressure loads being jacked into the structure, stresses are maintained at safe levels.
- C) Geometry Measurements -- critical geometric relationships are monitored in conjunction with strains and jacking pressure by means of dial indicators, tape measurements and extensimeters. This ensures that displacement of structural members under load agrees with predictions during the jacking operation.

6. Structural Repair

In preparation for removal of the damaged lower chord member it was necessary to cut out part of the roadway on each side to provide access. This removal was done in advance of the repair to facilitate measurements, inspection and preparation. Jersey barriers were placed along side the openings so that two lanes of traffic could be safely maintained in each direction.

During the preparation phase the activities included:

- Installation of strain gages
- Removal of rust and paint from riveted connections
- Replacement of rivets with bolts
- Placement (but not installation) of temporary chords
- Shop fabrication of new steel and jacking components

The 145th St. Bridge is a very active crossing between Manhattan and the Bronx. It was necessary to perform our repair with no live load on the bridge, yet any closing of the bridge had to be minimized. We estimated we would require four days and planned to start on a Friday after the evening rush hour and finish sometime the following Tuesday night.

To work within this time frame, one of the most important preparation tasks was to replace all rivets that would need removal with high strength bolts. Some of these high strength bolts were temporary in that they would be in turn removed and replaced when the new steel chord was installed, while the bridge was in the jacked up position.

Also during the preparation phase, the new replacement chord steel was fabricated in the shop. Shop drawings for this critical member were prepared by Harlem River Bridges section's maintenance engineers and approved by Hardesty and Hanover. It was essential that this member and all connection holes be accurate. The success of the entire repair depended on this member being installed easily and fitting properly. Each end connection had to match 100 existing connection bolt locations. To accomplish this, holes were punched using portable 'hougen' drills and

the existing end connection plate as a template. Other than the field drilling of end connection and holes, the entire lower chord was fabricated and assembled in our shop, then dismantled for delivery to the bridge site.

7. Jacking Operation

As mentioned earlier, the jacks utilized for this repair were 50 ton capacity, 5/8" stroke and rated at 10,000 psi. A total of 24 jacks, four per end lift were required. Special weldments and assemblies were designed and fabricated to provide adequate bearing surface at each end lift location. These components included steel blocks (rests) to transmit the jack load to the end lift housing.

The expected total jacking distance was anticipated to be about three inches. To accomplish this, 1/2" shim packs were prepared. For shim material, cold drawn steel was used to insure that the individual shims were as flat as possible. Shim thickness varied from 1/16" to 3/8".

The jacking sequence was as follows:

- 1) Raise the end lifts and insert shims as required under the end lift wheel to achieve a level condition at all six end lifts. This would be the base line or starting point.
- 2) Take a "zero" reading for all strain gages.
- 3) Jack the bridge 5/8" at all jacking points and record hydraulic pressure.
- 4) Insert 1/2" steel shims under the end lift wheel
- 5) Lower the bridge (approximately 1/8") by releasing the jack pressure, take strain gage and dial gage readings.
- 6) Reshim under jacks to prepare for next lift.

The jacking operation was continued until the following conditions were achieved:

- Average jacking height = 2"
- Average maximum jacking pressure = 8,000 psi.
- Average jacking load = 160 tons (per end lift)
- Average force in the center upper chord = 380 kips

It was judged by the consultant that these conditions were the closest we could obtain for safe removal and replacement of the damaged steel.

During the jacking operation, it was noticed that the strain readings in the lower chord members were considerably lower than the readings in the upper chord. This effect was due to the contribution to stiffness of the lower chord by the filled-in grating concrete deck and the steel longitudinal stringers, which were found to be continuous. As can be seen in Figs. 8 and 9, the force in the upper south chord is about 440 kips compared to 135 kips in the lower south chord. This extra stiffness of the lower chord prevented us from achieving the anticipated dimension of 24'-0" between panel points of the lower middle chord.

By jacking the temporary chord tube member, we attempted to force the panel points apart. When this was not successful, we also placed jacks in the two tee members of the temporary chord but the best we could achieve between panel points was 23'-11 5/8" or 3/8" short of the desired dimension. We could not overcome the tremendous stiffness caused by the concrete bridge deck and steel framing system. This would require minor modification to the replacement steel to make it fit. Since all connection holes for the new steel were to be field measured and drilled, this did not cause a significant problem.

Once the desired jacking condition was reached, the temporary chord was engaged to hold the bridge middle truss in position while the repair work was being done. Engaging the temporary chord was done by tightening all bolts in the three members (tube section and two tee sections).

It was then safe to begin removal of the damaged chord. High strength bolts were removed one at a time and replaced with temporary drift pins. This allowed the splice plates to be removed, followed by flame cutting, dismantling and removal of the damaged steel chord webs.

8. Installation of New Chord

As mentioned above, the center-to-center spacing between panel points was 3/8" less than anticipated. The new replacement chord was fabricated to 24'-0" in length (see Fig 7.). The webs were trimmed slightly in the shop and brought to the site. Final fit was accomplished by trial and error, grinding, and beveling of interfering edges and using sledges to force the web plates into place.


The bolt hole pattern in the existing steel was back-punched onto the new steel. The holes were drilled at the site using portable magnetic drills. Some reaming was required for final installation and bolts were installed hand tight. Top, bottom and flange angles were installed at this time. Before bolts were tightened, it was necessary to take out any residual slack or 'slop' in the new chord steel so there would be no slippage during load transfer. This slack was taken up by pressurizing the temporary chord jacks to approximately 8,500 psi.


VI SUMMARY

The repair of the fire damaged 145th Street Bridge described in this paper was the most complex and technically demanding project undertaken by the in-house Maintenance section in my ten years with the New York City Bureau of Bridges. We demonstrated in-house expertise in many areas including movable bridges, jacking, shop drawing preparation, structural fabrication, strain gages and instrumentation, electrical installation and repair and mechanical work.

The details of each of these activities and the relationship to the total repair could provide material of interest for several technical papers. What I have attempted to present here is an overview of a multi-faceted bridge repair project that was done completely in-house by the New York City Bureau of Bridges Maintenance Division with engineering support by a well known consultant. The timely success of the repair is a testament to the planning, cooperation and professional competence of all who were involved.

APPENDIX





ITEM NO.	QUANTITY	DESCRIPTION	MANUFACT	REMARKS
1		STANDARD LIFT PUMP	ENRPAAC	
2		ELECTRIC PUMP EEP-450	ENRPAAC	
3		ELECTRIC PUMP EEP-450	ENRPAAC	
4		ELECTRIC PUMP EEP-450	ENRPAAC	
5		HYDRAULIC PUMP	ENRPAAC	
6		HYDRAULIC PUMP	ENRPAAC	
7		HYDRAULIC PUMP	ENRPAAC	
8		HYDRAULIC PUMP	ENRPAAC	
9		HYDRAULIC PUMP	ENRPAAC	
10		HYDRAULIC PUMP	ENRPAAC	
11		HYDRAULIC PUMP	ENRPAAC	
12		HYDRAULIC PUMP	ENRPAAC	
13		HYDRAULIC PUMP	ENRPAAC	
14		HYDRAULIC PUMP	ENRPAAC	
15		HYDRAULIC PUMP	ENRPAAC	
16		HYDRAULIC PUMP	ENRPAAC	
17		HYDRAULIC PUMP	ENRPAAC	

145 ST. BRIDGE
END LIFT JACKING SYSTEM
MAIN SCHEMATIC

CITY OF NEW YORK
DEPARTMENT OF TRANSPORTATION
BUREAU OF BRIDGES

CONTRACT NO.

BOROUGH OF MANHATTAN B.I.N. 2-21008-9

PREPARED BY N.D.H. DRAFTER
IN CHARGE M. BRUMO CHECKER

FILE NUMBER

ORIGINAL SIZE IN INCHES

N. Y. C. D. O. T. MICROFILM IDENTIFICATION NUMBER

DRAWING NAME JACKING


DWG. NO. 1

SCALE NONE

DATE 9/20/59

SHEET

TABLE-1



NOTES:

1. STRESS IN CHORD IN PSI.

$$= \text{STRAIN}(\text{in./in.}) \times 30 \times 10^6 \text{ (Young's modulus)}$$

2. FORCE IN CHORD IN LBS.

$$= \text{CHORD AREA}(\text{in.}^2) \times \text{STRESS}(\text{PSI})$$

a) EXISTING LOWER CHORD AREA = 60.80 in.²

b) EXISTING UPPER CHORD AREA= 70.17 in.²

C) NEW CHORD AREA=

d) "T" SHAPED TEMPORARY

CHORD AREA = 12.0 in.²

CHORD AREA = 14.4 in.²

1000

14-00000

JACKING DISPLACEMENT

DATE	TEST	1	2	3	4	5
JAN 21	TEST					

[illegible]

LEV
XENN

LIF LIF LIF LIF LIF LIF

TOT

[illegible]
$$\frac{0}{-} \quad \frac{3}{-} \quad \frac{3}{-} \quad \frac{3}{-} \quad \frac{3}{-} \quad \frac{5}{-}$$
[illegible]

1	3	3	3	3	2	0.76
---	---	---	---	---	---	------

[illegible]

	-	3	3	3	3	3	2	3	0.39
--	---	---	---	---	---	---	---	---	------

68	68	68	68	68	2
----	----	----	----	----	---

[illegible]

16	4	8	8	8	16
----	---	---	---	---	----

1	1	3	3	3	3	2	0.76
---	---	---	---	---	---	---	------

4	4	8	8	8	8
---	---	---	---	---	---

3	3	3	3	3	0 30
3	3	3	3	3	1
3	3	3	3	3	2

[illegible]


1

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
84


JACKING DISPLACEMENT


JACKING POINTS	LEVELLING (REFERENCE POINTS)	LIFT #1	LIFT #2	LIFT #3	LIFT #4	LIFT #5	TOTAL	JAN 27 TEST DISPLACEMENT AFTER FAR LIFT BETTERMENT (IN)
A	$\frac{1}{8}$	—	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{15}{8}$	0.99
B	$\frac{1}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	2	0.76
C	$\frac{2}{1}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$2\frac{3}{8}$	0.39
D	$\frac{1}{16}$	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$1\frac{13}{16}$	0.99
E	$\frac{1}{4}$	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	2	0.76
F	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$\frac{3}{8}$	$2\frac{1}{4}$	0.39

JANUARY 7, 1971									
FRIDAY									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									
STRAIN DATE									
STRAIN TIME									
STRAIN LOCATION									
STRAIN TYPE									
STRAIN STATUS									
STRAIN COMMENTS									
STRAIN NAME									



TEMPORARY CHORD
MEMBERS








FIG. 7

FORCE CHANGE/ END LIFT DISPLACEMENT UPPER CHORDS BEFORE REPAIR




FIG. 8

FORCE CHANGE/END LIFT DISPLACEMENT LOWER CHORDS BEFORE REPAIR




FIG. 9

FORCE CHANGE/END LIFT DISPLACEMENT **UPPER CHORDS AFTER REPAIR INCLUDING** **JANUARY 27/94 OPENING TEST**




FIG. 10

FORCE CHANGE/END LIFT DISPLACEMENT

LOWER CHORDS AFTER REPAIR INCLUDING

JANUARY 27/94 OPENING TEST DATA




FIG. 11